



HOW TO APPLY SMART CHALKBOARD PAINT

Smart Chalkboard Paint is suitable for use on plaster, wallboards, wood, metal and concrete. Each tin covers up to 4 s.q.metres/ 43 s.q. feet (based on 2 coats). For interior use only.

1

MEASURE YOUR AREA

Measure the area accurately ensuring you have enough paint

2

PREPARE THE SURFACE

- All surfaces to be painted should be clean, dry and free from loose materials
- Clearly mark the area you wish to paint using masking tape
- Prime bare, untreated surfaces with [Smart White Primer](#)
- Once primed, lightly sand the surface

3

HOW TO APPLY CHALKBOARD PAINT

- Stir paint thoroughly before use
- For best results, apply paint using a foam roller
- Paint the surface using light even strokes, covering 1 metre sections at a time
- Apply 2 coats allowing first coat to dry before applying the second coat (approx. 2 hours)

4

DRYING TIME

Smart Chalkboard Paint will be touch-dry in 1 hour and usable after 24 hours

5

PREPARATION BEFORE USE

Before writing on the surface for the first time, condition the surface by rubbing the side of a stick of chalk all over the surface and erasing immediately with a dry cloth or eraser

6

ONGOING CLEANING

Your chalkboard surface can be cleaned with a [micro-fibre eraser cloth](#). A chalky residue will remain when cleaning with a dry cloth or eraser. This can be removed by using a damp cloth

Support:

Email:
support@smartersurfaces.com

Website:
www.smartersurfaces.co.uk



APPLICATION GUIDE



This surface will be ready to use within 24 hours.

I will become a Smarter Surface on:

Day _____ Date _____ Month _____



Support:

Email: support@smartersurfaces.com

Website:

www.smartersurfaces.co.uk